

LARGE, 7" WVGA, TOUCH-SCREEN INTERFACE
WINDOWS XP UMPC INTEL PENTIUM TABLET
60 GB INTERNAL HDD STORAGE
CHANNEL POWER MEASUREMENTS IN dBm
PEAK SEARCH / HOLD WITH UP 4 PEAK HOLD WAVEFORM TRACES
USER SELECTABLE POWER TRIGGERS
SPECTROGRAM / HISTOGRAM MEASUREMENTS
WAVEFORM JPEG SNAPSHOTS WITH PREVIEW & PRINTOUT

HONEYCOMB™ INTERFERENCE MAPPING SOFTWARE SUPPORT

ware while still in the field or later as a desktop application.

Bee™-TABLET hard-

DESTRICT



Berkeley Varitronics Systems 255 Liberty Street, Metuchen, NJ 08840 (732) 548-3737 / Fax: (732) 548-3404 www.bvsystems.com



Frequency Support:

BumbleBee TABLET Model 1: (P/N 0092-T-K0Y)

BumbleBee TABLET Model 2: (P/N 0092-T-Z0Y)

902.40-928.00 MHz (ISM) 2.4-2.5 GHz (ISM) 2.4-2.5 GHz (ISM) 4.9-5.9 GHz (Publi

5.150-5.900 GHz

4.9-5.9 GHz (Public Safety-(UNII))

## BumbleBee Receiver Specifications

**Span:** 1 MHz (750 MHz for Model 1) (1 GHz for Model 2) Resolution bandwidth: 50 kHz - 1 MHz (50, 100, 300, 500, 1 MHz)

UNII)

Channel Presets 802.11A/B/G/ZigBee/UNII Bands Video bandwidth (smoothing): 100 kHz - 1 MHz (50 kHz steps)

Screen Averaging: 1 – 100 Averages
Reference Stability: + 2.5 PPM

Sweep Time: 468 msec (100 MHz span, 50 kHz resolution bandwidth)

Amplitude:

Average Noise Floor (No input): < -100 dBm (reference level -70 dBm, Resolution BW=50 kHz)

Dynamic Range: > 40 dB

Level Accuracy:  $\pm$  1.5 dB (25 deg. C)

Max input (safe): + 0 dBm Max input (no saturation) - 20 dB

Reference level: -20 to -70 dBm (10 dB steps)

Waveform Displays/GUI:

Number of traces: 1 live + 4 peak hold with ability to freeze up to 4 instances of peak & live traces

Trace settings: Peak hold, screen average, freeze trace (live/peak/average)

Marker functions: Up to 3 pairs of delta markers

Picture-In-Picture: Mini-view to simultaneously view live & average

Triggering:

Auto or Manual: Trigger the receiver & make measurements of live & peak traces when input power meets or exceeds trigger threshold (20 MHz span)

Trigger threshold: user settable in dBm.

Trigger delay: user settable in nanoseconds

Input Connector: SMA Female,  $50\Omega$ 

Power:

Internal battery: (4 AA Ni-MH), AC or DC

Run time (internal battery): > 3 hours Re-charge time: < 1 hour

Physical Specifications:

Weight: 1 lb.

Dimensions: 4"H x 3"W x 6"L

Tablet Specifications

Manufacturer: Samsung (Q1)

CPU: Intel Pentium M ULV 723 1GHz (specify requirements when ordering)

LCD: 7" WVGA

Operating System: Windows XP UMPC Tablet Edition

 VRAM:
 Shared

 Memory:
 1GB DDR 400

 HDD:
 60GB (4200 RPM)

 ODD:
 None

 Wired:
 100MB LAN

 Built-In Wireless:
 802.11g+BT

**Physical Specifications:** 

Weight: 1.7 lb.

Dimensions: 1"H x 5"W x 9"L